

Components

PIPEGUARD® CMH ACCESSORIES

FOR USE WITH CONSTANT-WATTAGE, METALLIC-SHEATHED, HIGH-TEMPERATURE HEATING CABLE

Drexan HeatTracer PipeGuard CMH Accessories are for installation with PipeGuard CMH Cable only.

CMH Connection Kit (Compression Type)

Cat.# CMH-CON (comes with 2 strain reliefs)

Cat.# CMH-PWR (comes with 1 strain relief)



CMH Termination Kit (Clamshell Type)

Cat.# CMH-TERM



CMH Lighted End Seal Kit

Cat.# CMH-LE-1/2R



Junction Box (Power and up to 3 heaters)

Cat.# HP-FG-JB



CMH-PAU (Pre-assembled Cable Unit)

Cat.# CMH-PAU



CMH End Seal

Cat.# CMH-RMES



CMH Low Profile End Seal

Cat.# CMH-LP-E



SPECIFICATIONS

AREA CLASSIFICATION

Non-hazardous and hazardous locations

TRACED SURFACE TYPE

Metal Pipes

SUPPLY VOLTAGE(S)

Refer to individual product data sheets or contact Drexan

MAXIMUM CABLE EXPOSURE (POWER OFF)

842°F/450°C

MINIMUM AMBIENT TEMPERATURE

-40°F/-40°C

APPROVALS

Refer to individual product data sheets or contact Drexan

FOR HEATTRACER TECHNICAL ASSISTANCE CALL 1-800-663-6873 (NORTH AMERICA ONLY) OR +1.780.413.1774