

## AMIGA-E



## AMIGA-LE




The AMIGA end seals provide a dependable method of terminating the ends of self-regulating cables. Available either lighted (LE) or non-lighted (E), the end seals are made from high-performance materials which resist impact, high temperatures and exposure to chemicals. The stanchion allows for up to 4 inches of insulation on the pipe and comes complete with two pipe straps for mounting.

### SPECIFICATIONS

ORDERING PART NOS.	AMIGA-E (no light)	AMIGA-LE (lighted)
HEATING CABLE TYPES	PipeGuard HOT (PGH), WARM (PG), MULTITRACE (MT)	PipeGuard HOT (PGH), WARM (PG), MULTITRACE (MT)
INGRESS PROTECTION	NEMA 4X (IP65) (IP66)	NEMA 4X (IP65) (IP66)
MINIMUM INSTALL TEMP.	-40 F (-40°C)	-40 F (-40°C)
MAX. EXP. (PIPE) TEMP	500 F (260 C)	500 F (260 C)
OPERATING VOLTAGE	120-277	120-277
LIGHT	N/A	Blue/Green
POWER CONSUMPTION	N/A	3 watts

### APPROVALS


 Class I, Div. 2, Groups A, B, C, D  
 231572 Class II, Div. 2, Groups E, F, G  
 Class III

FOR HEATTRACER TECHNICAL ASSISTANCE CALL 1-800-663-6873 (NORTH AMERICA ONLY) OR +1.780.413.1774